

E-BOX 48100R-C TE+ LB



Features



Scalable

- From 5.12kWh to 491.52kWh



Compact, Flexible and Easy Install



Long-lasting

- ≥ 6000 Cycles @ 90% DoD
- 10 years warranty



Safe & Reliable

- Tier 1 Automotive Grade A LiFePO4 cells
- Self-designed & Field-proven BMS



1C Discharge

- Simultaneously supplying power to multiple loads, no need to worry about power outages



48100R-C TE+ LB Specs

Electrical

Nominal Voltage	51.2V
Voltage Range	47.5V~57.6V
Nominal Capacity	100Ah
Nominal Energy	5.12kWh
Recommended Charge/	50A (2.56kW dc)
Discharge Current	
Maximum Charge/	Charge:50A/ Discharge 100A
Discharge Current	
Peak Discharge Current	102A (5.22kW@15s)

General

Chemistry	LFP
Communication Protocol	CAN/RS485
Dimensions (L x W x H)	440 x 620 x 117mm (2.6U) / 17.3 x 24.4 x 4.6 inch (2.6U)
Weight	51 kg / 112.5 lbs
Ambient Temperature	-10°C~50°C / 14°F~122°F
Round-Trip Efficiency	≥ 95%
Cycle Life*	≥ 6000Cycles
Warranty	10 Years

* Test Condition 0.5C, 25°C @90%DoD

Certifications

UL9540 Ed.2 (2020), UL9540A, UL1973, CEC, SGIP, CE, IEC62619, UN38.3